

TO: FOOD OPERATORS, CONTRACTORS, and DESIGNERS
FROM: PLAN REVIEW AND CONSTRUCTION UNIT
CONSUMER PROTECTION DIVISION
DEPARTMENT OF ENVIRONMENTAL HEALTH
DATE: OCTOBER 1, 2002
SUBJECT: FOOD FACILITY APPROVED CEILING MATERIALS

No one ceiling material is suitable for every type of application. When selecting a ceiling material for a particular application, several things, such as type and frequency of maintenance, sound attenuation, fire control, etc., should be taken into account. If you have any doubt as to the suitability of a product for an application, verify it with the manufacturer.

The following types of ceiling materials are approved for use and meet the requirements for installation within the following areas:

1. Food preparation, packaging, dispensing or storage rooms where food is stored in open containers.
2. Utensil washing.
3. Refuse or garbage storage.
4. Janitorial facilities.
5. Toilet and handwashing locations.
6. Employee change and clothing storage.

GYPSON PANELS - Used in typical "T" bar suspended ceilings

CAPPAUL VINYLOCK 1/2" thick VINYLOCK II 5/16" thick	Custom Acoustic 859 Savaker Street San Jose, CA 95126 (408) 298-5758	Dudley Acoustic 424 Lono Street San Jose, CA 95125 (408) 292-3961
NATIONAL GYPSUM COMPANY- Gridstone Gypsum Lay-in Grid Panels	Railway Distributing 264 Railway Avenue Campbell, CA 95008 (408) 866-9266	
NATIONAL GYPSUM COMPANY - Gold bond Building Products	Railway Distributing 264 Railway Avenue Campbell, CA 95008 (408) 866-9266	
USG STIPPLE WHITE #3270	Bay Supplies Ceiling 30900 Huntwood Hayward, CA 94544 (510) 489-4441	Ceiling Systems Supply 500 Indiana Street San Francisco, CA 94107 (415) 861-2080

Wills Materials
954 Chestnut Street
San Jose, CA 95110
(408) 297-9192

GYPROC LAY-IN CEILING PANELS

Bay Supplies Ceiling
30900 Huntwood
Hayward, CA 94544
(510) 489-4441

OTHER SUSPENDED CEILING PRODUCTS

ARMSTRONG

Ceramaguard RH100 (Non-perforated, plain only)

Clean Room VL (Non-perforated only)

Mylar RH90 Fire Guard

USG Ceilings CLEAN ROOM *CLIMAPLUS*

Class 100 Ceilings

Armstrong Commercial Ceilings 1(888)-CEILINGS

Armstrong Commercial Ceilings 1(888)-CEILINGS

Armstrong Commercial Ceilings 1(888)-CEILINGS

White color only

GYPSUM BOARD

Gypsum board may be used, however, it must be smooth finished and painted with a light-colored enamel or semi-gloss paint. The chosen color must have a light reflectance value of 70% or greater. Textured gypsum board surfaces are not acceptable.

PLASTER

Plaster may be used. The finish shall be smooth (non-textured) and light in color. The chosen color must have a light reflectance value of 70% or greater.

The above information has been provided by the manufacturers/distributors. No warranty is expressed or implied.

Be sure to contact your local Building or Fire Officials regarding the use and installation of the above materials