



SECTION B/2 - B/2

**PRE-CAST CONCRETE CURB INLET NOTES**

- All exposed metal parts shall be hot dipped galv. after fabrication.
- Concrete shall develop a strength of 21 MPa (3000 psi) at 28 days.
- Top and cover shall be reinforced with 100 mm x 100 mm (4"x4") - 6-6 wire mesh.
- Weight of unit complete = 590 kg (1300 lbs)±  
Weight of cover only = 36 kg (80 lbs)±
- CURB INLET:  
Santa Rosa Cast Products Co. model 4-A,  
or approved equal by Road Commissioner.

METRIC (& ENGLISH) UNITS

NO.	REVISIONS	BY	DATE	APP'D



**SANTA CLARA COUNTY ROADS AND AIRPORTS DEPARTMENT**

DESIGNED VAP 09/22/97	DATE 09/22/97	WORK ORDER	SUBMITTED:	APPROVAL:
DRAWN LRE 09/22/97	DATE 09/22/97	LEVEL BOOK		
CHECKED VAP 09/22/97	DATE 09/22/97	TRANSIT BOOK		

**STANDARD DETAILS  
DRAINAGE INLET  
TYPE C-4 WITH GALLERY**

PROJECT NO.	CONTRACT NO.	FILE NO.

DRAWING NO. <b>C</b>
SHT. NO. <b>5</b>
2 of 3